

Cessna 172SP checklist

Pre-Start

Parking Brakes	SET
Cabin doors	CLOSED
Throttle	CLOSED
Magneto/Starter Switch	OFF
Batt. & Alt. Master Switches	OFF
Avionics	OFF
Fuel Pump Switch	OFF
Mixture /Fuel Flow	CUTOFF
Battery Switch	ON
Flight controls	CHECK
Flaps	UP
Fuel Quantity	CHECK
Fuel Selector	BOTH
Avionics Switch	ON
Navigation Light	ON
Request Clearance	
Transponder	STANDBY
Beacon Light	ON

Starting Engine

Fuel pump.....	ON
Start Key	BOTH
Throttle.....	OPEN 1/4 INCH
Mixture	RICH
Via dall'elica !	
Start Key	START!
Alt. Master Switch	ON
Oil Pressure & Ammeter	CHECK
Fuel pump.....	OFF
Altimeter	SET

Taxing

Taxi Light	ON
Parking Brakes	RELEASE
Low-speed !	

Before Takeoff

Squawk	7000(for VFR)
Flaps	10°
Trim	set for T.O.
Landing Light	ON
Strobo Light	ON

After Takeoff

Flaps	UP
Landing Light	OFF
Standard Climb at 80 KIAS	

Approach

Fuel selector	BOTH
Mixture	RICH
Landing Light	ON
Altimeter	SET
Airspeed 70 KIAS (flaps down)	

Parking

Parking Brakes	SET
Avionics Switch	OFF
Flaps	UP
Mixture	0%
Light (ALL).....	OFF
Batt. & Alt. Master Switches	OFF
Start Key	OFF